



Fuse-link, high speed, 315 A, AC 1250 V, 100 kA, size 3, 76 x 92 x 139 mm, aR, DIN, IEC, type K indicator



Part no. FUSE 315A 1250V 3KN/110 AR CU
Catalog No. 170M6238

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	315
Rated voltage			AC 1250 V
Construction size			size 3
Size			76 x 92 x 139 mm
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			3
Type of current			AC
Rated voltage AC		V	1250
Rated voltage DC		V	
Rated current		A	315
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	100
Colour code			None
Type of fuse status indicator			Other
Power loss at rated current		W	85
Mounting holes			M10
Centre-to-centre distance of connections		mm	108