



Fuse-link, LV, 20 A, AC 400 V, 8 x 31 mm, gL/gG, IEC, indicating

Catalog No. C08G20I

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	20
Rated voltage			AC 400 V
Size			8 x 31 mm
Utilization category			gL/gG
Status indicator			with indicator
Breaking Capacity		kA	20
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			Other
Rated voltage		V	400 - 400
Rated voltage			Other
Voltage type			AC
Utilization category			gL/gG (cable protection/equipment protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	20
With striker			No
Release characteristic			Other
Breaking capacity		kA	20

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusssmann.com/pdf/7eba542b-1b11-4a86-afd0-69ed8f8a374b.pdf
-------------------------	---