

Specifications



Eaton C22M100S

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 100 Amps, 120 kA Breaking capacity, class aM, with striker, compatible with a CH22 Modular fuse holder

General specifications

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C22M100S
MODEL CODE	CYL FUSE >STR >22 x 58 100A AM 500V AC
UPC	051712666879
EAN	5027590495653
PRODUCT LENGTH/DEPTH	22 mm
PRODUCT HEIGHT	22 mm
PRODUCT WIDTH	58 mm
PRODUCT WEIGHT	55.9 g
WARRANTY	1 year limited
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	IEC 60269

Product specifications	
TYPE	fuse
SPECIAL FEATURES	Striker
APPLICATION	- for industrial applications - for general purpose use
AMPERAGE RATING	100 A
FITTED WITH:	Striker
FUSE SIZE	22 x 58 mm
CURRENT TYPE	AC
BREAKING CAPACITY	120 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	500 V
CLASS	Class aM
FUSE TYPE	C22M
UTILIZATION CATEGORY	aM (switchgear protection)
FUSE INDICATOR	Top fuse status indicator
WATT LOSSES	6.61 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	22 mm x 58 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CH22 Modular fuse holder
MATERIAL	Ceramic
MOUNTING METHOD	22 x 58 mm CH Modular fuse holder
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	500 V

PROJECT NAME:

Resources	
	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CATALOGS	eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf Bussmann series complete full line catalog no. 1007
DECLARATIONS OF CONFORMITY	UKCA C08G, C08M, etc cylindrical fuselinks CE C08G, C08M, etc cylindrical fuselinks
TECHNICAL DATA SHEETS	720115 Cylindrical fuses

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights
Reserved.

Eaton is a registered trademark.

All other trademarks are property of
their respective owners.

Follow us on social media to get the latest
product and support information.

