

DATASHEET - FUSE 550A 1250V 2/110 AR CU



Fuse-link, high speed, 550 A, AC 1250 V, 100 kA, size 2, 61 x 75 x 138 mm, aR, DIN, IEC, single indicator



Part no. FUSE 550A 1250V 2/110 AR CU
Catalog No. 170M5145

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	550
Rated voltage			AC 1250 V
Construction size			size 2
Size			61 x 75 x 138 mm
Utilization category			aR
Status indicator			single indicator
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecI@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			2
Type of current			AC
Rated voltage AC		V	1250
Rated voltage DC		V	
Rated current		A	550
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	100
Colour code			None
Type of fuse status indicator			Top fuse status indicator
Power loss at rated current		W	100
Mounting holes			M10
Centre-to-centre distance of connections		mm	108