

Fuse-link, low voltage, 800 A, AC 500 V, 120 kA, NH4, gL/gG, IEC, single indicator, live gripping lugs

Part no. 500V 800A NH4 FUSE AG
Catalog No. 800NHG4G

EL-Nummer 1664092
(Norway)

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	800
Rated voltage			AC 500 V
Construction size			NH4
Utilization category			gL/gG
Status indicator			single indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with slotted blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 (AFZ800015))			
Fuse construction type according to IEC 60269			NH4
Voltage type			AC
Rated current		A	800
Rated voltage AC		V	500
Rated voltage DC		V	
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No
Power loss at rated current		W	

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/dd9b7025-0e58-46b4-b717-66ce5e12c2b8.pdf
-------------------------	---