

DATASHEET - FUSE 1100A 1250V 23BKN/75 AR



Fuse-link, high speed, 1100 A, AC 1250 V, 2 x size 3, 74 x 52 x 167 mm, aR, IEC, single indicator



Part no. **FUSE 1100A 1250V 23BKN/75 AR**
Catalog No. **170M6789**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1100
Rated voltage			AC 1250 V
Construction size			2 x size 3
Size			74 x 52 x 167 mm
Utilization category			aR
Status indicator			single indicator
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC Rated

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecI@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			AC
Rated voltage AC		V	1250
Rated voltage DC		V	
Rated current		A	1100
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	125
Colour code			None
Type of fuse status indicator			Other
Power loss at rated current		W	220
Mounting holes			M10
Centre-to-centre distance of connections		mm	75