

DATASHEET - FUSE 800A 750VDC A3/A130 PC GR



Fuse-link, high speed, 800 A, DC 750 V, 110 kA, size 3, 75 x 88 x 131 mm, gR, IEC, type K indicator



Part no. FUSE 800A 750VDC A3/A130 PC GR
Catalog No. 170M2016

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	800
Rated voltage			DC 750 V
Construction size			size 3
Size			75 x 88 x 131 mm
Utilization category			gR
Status indicator			type K indicator
Breaking Capacity		kA	110
usable for size/applications			traction third rail
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			
Rated voltage AC		V	
Rated voltage DC		V	750
Rated current		A	800
Utilization category			gR (general purpose semiconductor protection)
Breaking capacity		kA	
Colour code			
Type of fuse status indicator			Other
Power loss at rated current		W	
Mounting holes			
Centre-to-centre distance of connections		mm	

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/2ef86aed-e370-419c-ad0a-89df8d9dab6c.pdf
-------------------------	---