



Fuse-link, LV, 1250 A, AC 500 V, NH4, gL/gG, IEC, single indicator, live gripping lugs

**EL Number
(Norway)**

**1250NHG4G
1664094**

Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		1250NHG4G
EAN		5027590429719
Product Length/Depth		200 millimetre
Product height		115 millimetre
Product width		102 millimetre
Product weight		2474 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269-2 IEC 60269-1 DIN 43620
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-ICP-BUSS-Eaton Bussmann series low voltage NH fuse
Globally Marketable		Yes

Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gG/gL

Fuse size		NH4
Insulated metal gripping lugs (IMGL)		No

Suitable for		SD4-S NH Fuse base EBH Size 00 to 4 Horizontal fuse switch-disconnectors
--------------	--	---

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH4
Voltage type		AC
Rated current	A	1,250
Rated voltage AC	V	500
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Top fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	108