



Fuse block, low voltage, 20 A, AC 600 V, DC 600 V, 41 x 31 x 76 mm, 2P, UL, CSA, Screw terminal

Part no. **BUSS FUSEBLOCK WAS 2919**
Catalog No. **BG3032S**

Delivery program

Product range			Fuse accessory
Basic function			Fuse-block
Field of application			low voltage
Rated current	I	A	20
Rated voltage			AC 600 V DC 600 V
Size			41 x 31 x 76 mm
Description			Screw terminal
Number of poles			2P
Standard/Approval			UL CSA
Standards/Regulations			Contact Manufacturer

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse base (EC000067)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low-Voltage HRC fuse base (ecl@ss10.0.1-27-14-21-06 [AKE278013])			
Construction size			Other
Number of poles			2
Rated current		A	20
Bus-mounting type			No
Swivelling mechanism			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_1106_BG_Series.pdf
-------------------------	---