

FUSE WSFL 10X85 30A 1K5V GPV**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

gPV 10×85 cylindrical fuse cartridges are designed to provide compact, safe and economical protection of photovoltaic modules (field protection) with voltages up to 1,500 DC. They provide protection against both overload and short circuit (gPV class according to the requirements of IEC60269-6 and UL248-19 standards).

General ordering data

Version	Photovoltaics, Cartridge fuse, 1500 V, 10x85, gPV, 30 A
Order No.	4000005431
Type	FUSE WSFL 10X85 30A 1K5V GPV
GTIN (EAN)	8430243440424
Qty.	50 pc(s).

FUSE WSFL 10X85 30A 1K5V GPV**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Height	85 mm	Height (inches)	3.346 inch
Width	10.3 mm	Width (inches)	0.406 inch
Net weight	0.2 g		

Fuse cartridge

Fuse-link standard	IEC 60269-6, gPV (EN 60269-6)	Current	30 A
Rated DC voltage	1,500 V	Rated breaking capacity	10 kA
Contact material	silver-plated	Power dissipation, max.	5.5 W

Classifications

ETIM 7.0	EC002704	ETIM 8.0	EC002704
ETIM 9.0	EC002704	ECLASS 11.0	27-14-20-02
ECLASS 12.0	27-14-20-02	ECLASS 13.0	27-14-20-02
ECLASS 14.0	27-14-20-02		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Approvals

ROHS	Conform
------	---------

Downloads

Catalogues	Catalogues in PDF-format
------------	--