

# EAO – Your Expert Partner for Human Machine Interfaces

## 82-6151.0234 - Indicator 22 mm stainless-steel

### 82-6151.0234 - Indicator 22 mm stainless-steel



*Attention: The preview is based on a sample product. This can differ from your current configuration.*

#### Mounting

|                  |           |
|------------------|-----------|
| Design           | flush     |
| Mounting cut-out | Ø 22,3 mm |

#### Front

|                      |                 |
|----------------------|-----------------|
| Front dimension      | Ø 25 mm         |
| Front shape          | round           |
| Front ring shape     | flush           |
| Front bezel material | Stainless steel |

#### Other Attributes

|                   |            |
|-------------------|------------|
| Operating voltage | 24 V AC/DC |
| Weight            | 0,021 kg   |
| Operation current | 7 mA       |

#### Operating-/Indication part

|                   |                 |
|-------------------|-----------------|
| Lens optics       | opaque          |
| Lens material     | Stainless steel |
| Lens profile      | flat            |
| Lens illumination | illuminative    |
| Lens colour       | Stainless steel |

#### IP-Rating

|                  |            |
|------------------|------------|
| Front protection | IP65, IP67 |
|------------------|------------|

#### Connection Method

|          |                     |
|----------|---------------------|
| Terminal | Solder 2.8 x 0.5 mm |
|----------|---------------------|

#### Illumination

|              |                    |
|--------------|--------------------|
| Illumination | Dot with green LED |
|--------------|--------------------|


#### Function

|           |
|-----------|
| Indicator |
|-----------|


# EAO – Your Expert Partner for Human Machine Interfaces

82-6151.0234 - Indicator 22 mm stainless-steel


## Dimensions



## Mounting cut-outs



## Wiring diagram



## Component layout

