

DATASHEET - FUSE 450A 1250V 1FU/115 AR CU



Fuse-link, high speed, 450 A, AC 1250 V, 100 kA, size 1, 53 x 69 x 160 mm, aR, IEC, UL, US style



Part no. **FUSE 450A 1250V 1FU/115 AR CU**
Catalog No. **170M4694**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	450
Rated voltage			AC 1250 V
Construction size			size 1
Size			53 x 69 x 160 mm
Utilization category			aR
Description			US style
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with centre-bolted tags
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			1
Type of current			AC
Rated voltage AC		V	1250
Rated voltage DC		V	
Rated current		A	450
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	100
Colour code			None
Type of fuse status indicator			None
Power loss at rated current		W	80
Mounting holes			Other
Centre-to-centre distance of connections		mm	114