

DATASHEET - FUSE 63A 690V 000TN/80 GR UC



Fuse-link, high speed, 63 A, AC 690 V, 200 kA, DIN 000, gR, DIN, IEC, type T indicator, square body with offset bolted tags (slotted)



Part no. **FUSE 63A 690V 000TN/80 GR UC**
Catalog No. **170M1415**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	63
Rated voltage			AC 690 V
Construction size			DIN 000
Utilization category			gR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with offset bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4
Optional accessories			fuse-holder 170H1007

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		000
Type of current		AC
Rated voltage AC	V	690
Rated voltage DC	V	
Rated current	A	63
Utilization category		gR (general purpose semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		Top fuse status indicator
Power loss at rated current	W	16
Mounting holes		M8
Centre-to-centre distance of connections	mm	78

Additional product information (links)

High-speed full-line catalogue (pdf)	http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf
--------------------------------------	---