

DATASHEET - FUSE 2400A 1250V 4BKN/110 AR



Fuse-link, 2400 A, AC 1250 V, 200 kA, size 4, 105 x 120 x 110 mm, aR, IEC, type K indicator



Part no. **FUSE 2400A 1250V 4BKN/110 AR**
Catalog No. **170M7107**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	2400
Rated voltage			AC 1250 V
Construction size			size 4
Size			105 x 120 x 110 mm
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	200
usable for size/applications			Protection of power rectifiers
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			4
Type of current			AC
Rated voltage AC		V	1250
Rated voltage DC		V	
Rated current		A	2400
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	200
Colour code			None
Type of fuse status indicator			Other
Power loss at rated current		W	255
Mounting holes			M10
Centre-to-centre distance of connections		mm	110