

DATASHEET - CYLINDRICAL FUSE 22 X 58 63A AM 690V AC



Fuse-link, low voltage, 63 A, AC 690 V, 80 kA, 22 x 58 mm, aM, IEC

Part no. **CYLINDRICAL FUSE 22 x 58 63A AM 690V AC**
Catalog No. **C22M63**

EL-Nummer
(Norway) **1600233**



Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	63
Rated voltage			AC 690 V
Size			22 x 58 mm
Utilization category			aM
Breaking Capacity		kA	80
usable for size/applications			motor protection for industrial applications
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])			
Model			Ceramic fuse
Size			22x58 mm
Voltage type			AC
Rated current		A	63
Rated voltage		V	690
Utilization category			aM (switchgear protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	80
Power loss at rated current		W	4.46