

DATASHEET - FUSE 630A 2000V 3BKN/140 AR



Fuse-link, high speed, 630 A, AC 2000 V, size 3, 74 x 96 x 143 mm, aR, IEC, type K indicator



Part no. FUSE 630A 2000V 3BKN/140 AR
Catalog No. 170M6637

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	630
Rated voltage			AC 2000 V
Construction size			size 3
Size			74 x 96 x 143 mm
Utilization category			aR
Status indicator			type K indicator
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	630
Rated voltage		V	2000
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No