

DATASHEET - FUSE 160A 1000V DC 000FU/90 AR UR



Fuse-link, high speed, 160 A, DC 1000 V, 50 kA, size 000, 24 x 36 x 115 mm, aR, IEC



Part no.
Catalog No.

FUSE 160A 1000V DC 000FU/90 AR UR
170M1810

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	160
Rated voltage			DC 1000 V
Construction size			size 000
Size			24 x 36 x 115 mm
Utilization category			aR
Breaking Capacity		kA	50
Standard/Approval			IEC
Shape			square body with offset bolted tags

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			000
Type of current			DC
Rated voltage AC		V	
Rated voltage DC		V	1000
Rated current		A	160
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	50
Colour code			None
Type of fuse status indicator			None
Power loss at rated current		W	37
Mounting holes			M8
Centre-to-centre distance of connections		mm	91